

**LED Dome Bollard with IES Type III Glass (LG)**

**Model: BOG3**

Extruded aluminum housing with flush mounting base and vandal-resistant screws, domed top, powdercoat finish over a chromate conversion coating, internal ballast tray for easy maintenance. IES Type III clear prismatic borosilicate glass refractor and clear polycarbonate lens. LED: 1 x 9 or 12w

**ORDERING**

BOG3	Description
L	L=LG Innotek
F	F=Medium Beam Spread
1X	1X=One
12	9=9w, 12=12w
U	U=120-277V
4K	3K=3000K, 4K=4000K, 57K=5700K, 65K=6500K
Z	Z=Bronze
W	W=White,
B	B=Black
OPTIONS:	
SF	SF=Single Fuse
DF	DF=Double Fuse
SP	SP=Surge Protection
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts
BOLPC	Replacement Polycarbonate Lens



Example: BOG3LF1X12U4KZSP

**SPECIFICATIONS**

**Housing:**  
Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance  
**Refractor:**  
IES Type III Clear Prismatic Borosilicate Glass  
**Reflector:**  
**Lens:**  
Clear Polycarbonate Lens  
**Mounting:**  
Mounting Kit with 8" Anchor Bolts (Included)  
LG LED Module:  
Luminous Flux: See Chart  
CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K  
Operating Temperature: -40 ~ 50°C

50,000 Hours  
Module has IP67 Rating  
RoHS Compliant  
Wattage:  
LED: 1 x 9 or 12w  
Driver:  
Electronic Driver, 120-277V, 50/60Hz  
Listing & Ratings:  
CSA: Listed for Wet Locations  
Options:  
Dimmable Driver  
2.5KV Surge Protection  
Custom Colors Available Upon Request.  
Bollards Can Be Cut To Custom Lengths Upon Request.

**LED Dome Bollard with IES Type III Glass (LG)**

**Model: BOG3**

Extruded aluminum housing with flush mounting base and vandal-resistant screws, domed top, powdercoat finish over a chromate conversion coating, internal ballast tray for easy maintenance. IES Type III clear prismatic borosilicate glass refractor and clear polycarbonate lens. LED: 1 x 9 or 12w

**Total Luminous Flux per Module**

Optic Type	CFI		12w		9w	
	12w	9w	12w	9w	12w	9w
CCT						
6500K	1288	850	1345	888	1296	856
5700K	1288	850	1345	888	1296	856
4000K	1076	710	1100	726	1088	718
3000K	1000	690	1030	705	1015	710



**SPECIFICATIONS**

<p><b>Housing:</b> Extruded Aluminum Housing with Flush Mounting Base &amp; Vandal-Resistant Screws, Domed Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance</p> <p><b>Refractor:</b> IES Type III Clear Prismatic Borosilicate Glass Refractor</p> <p><b>Lens:</b> Clear Polycarbonate Lens</p> <p><b>Mounting:</b> Mounting Kit with 8" Anchor Bolts (Included)</p> <p><b>LG LED Module:</b> Luminous Flux: See Chart CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K Operating Temperature: -40 ~ 50°C</p>	<p>50,000 Hours</p> <p>Module has IP67 Rating</p> <p>RoHS Compliant</p> <p><b>Wattage:</b> LED: 1 x 9 or 12w</p> <p><b>Driver:</b> Electronic Driver, 120-277V, 50/60Hz</p> <p><b>Listing &amp; Ratings:</b> CSA: Listed for Wet Locations</p> <p><b>Options:</b> Dimmable Driver 2.5KV Surge Protection Custom Colors Available Upon Request. Bollards Can Be Cut To Custom Lengths Upon Request.</p>
---	--