

LED Dome Bollard with IES Type V Glass (LG)

Model: BOG5

Extruded aluminum housing with flush mounting base and vandal-resistant screws, domed top, powdercoat finish over a chromate conversion coating, internal ballast tray for easy maintenance. IES Type V clear prismatic borosilicate glass refractor and clear polycarbonate lens. LED: 1 x 9 or 12w

ORDERING

BOG5	Description
L	L=LG Innotek
F	F=Medium Beam Spread
1X	1X=One
12	9=9w, 12=12w
U	U=120-277V
4K	3K=3000K, 4K=4000K, 57K=5700K, 65K=6500K
Z	Z=Bronze
W	W=White,
B	B=Black
OPTIONS:	
SF	SF=Single Fuse
DF	DF=Double Fuse
SP	SP=Surge Protection
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts
BOLPC	Replacement Polycarbonate Lens



Example: *BOG5LF1X12U4KZSP*

SPECIFICATIONS

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance

Refractor:

IES Type V Clear Prismatic Borosilicate Glass

Reflector

Lens:

Clear Polycarbonate Lens

Mounting:

Mounting Kit with 8" Anchor Bolts (Included)

LG LED Module:

Luminous Flux: See Chart

CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K

Operating Temperature: -40 = 50°C

50,000 Hours

Module has IP67 Rating

RoHS Compliant

Wattage:

LED: 1 x 9 or 12w

Driver:

Electronic Driver, 120-277V, 50/60Hz

Listing & Ratings:

CSA: Listed for Wet Locations

Options:

Dimmable Driver

2.5KV Surge Protection

Custom Colors Available Upon Request.

Bollards Can Be Cut To Custom Lengths

Upon Request.

LED Dome Bollard with IES Type V Glass (LG)

Model: BOG5

Extruded aluminum housing with flush mounting base and vandal-resistant screws, domed top, powdercoat finish over a chromate conversion coating, internal ballast tray for easy maintenance. IES Type V clear prismatic borosilicate glass refractor and clear polycarbonate lens. LED: 1 x 9 or 12w

**Total
Luminous Flux
per Module
Optic Type
C F I**

	12w	9w	12w	9w	12w	9w
CCT						
6500K	1288	850	1345	888	1296	856
5700K	1288	850	1345	888	1296	856
4000K	1076	710	1100	726	1088	718
3000K	1000	690	1030	705	1015	710



SPECIFICATIONS

<p>Housing: Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance</p> <p>Refractor: IES Type V Clear Prismatic Borosilicate Glass Refractor</p> <p>Lens: Clear Polycarbonate Lens</p> <p>Mounting: Mounting Kit with 8" Anchor Bolts (Included)</p> <p>LG LED Module: Luminous Flux: See Chart CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K</p>	<p>Operating Temperature: -40 ~ 50°C 50,000 Hours Module has IP67 Rating RoHS Compliant</p> <p>Wattage: LED: 1 x 9 or 12w</p> <p>Driver: Electronic Driver, 120-277V, 50/60Hz</p> <p>Listing & Ratings: CSA: Listed for Wet Locations</p> <p>Options: Dimmable Driver 2.5KV Surge Protection Custom Colors Available Upon Request. Bollards Can Be Cut To Custom Lengths</p>
---	--