

LED Dome Bollard with Louvers

Model: BOL3

Extruded aluminum dome-top LED bollard with powdercoat finish, cast aluminum louvers, and clear polycarbonate lens. Housing features a flush mounting base, vandal resistant screws, and an internal ballast tray. Mounting kit with 8" anchor bolts included. Maximum 2x15w LED

ORDERING

BOL3	Description
X	Xicato
3X	Three LED Modules
2X	Two LED Modules
15H	15 Watts *Not available in 3 module units
7H	7.5 Watts
U	120, 277, 347 or 480 Volts
4	4000K
Z	Bronze
W	White
B	Black
OPTIONS:	
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts
BOLPC	Replacement Polycarbonate Lens

Example:
BOL3X3X7HU4Z



SPECIFICATIONS

Housing:
Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance
Reflector:
Cast Aluminum Louvers
Lens:
Clear Polycarbonate Lens
Mounting:
Mounting Kit with 8" Anchor Bolts (Included)
Xicato LED Module:
Luminous Flux: 1070lm @ 500mA (83 lpw), 780lm @ 350mA (88 lpw)

CRI: ≥ 80 , CCT: 4000K
Operating Temperature: -40°C to 80°C {@ Tc}
50,000 Hours
Module has IP66 Rating
RoHS Compliant
1x2 MacAdam Ellipse Color Specification
Wattage:
LED: 2 x 7.5 or 15w, 3 x 7.5w
Listing & Ratings:
CSA: Listed for Wet Locations
Custom Colors Available Upon Request.
Bollards Can Be Cut To Custom Lengths Upon Request.