

LED Dome Stainless Steel Bollard with Louvers (LG)

Model: BOLSS

Formed 316 Stainless Steel Housing with Flush Mounting Base and Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance. Cast Aluminum Louvers with Clear Polycarbonate Lens.

LED: 1 x 9 or 12w

ORDERING

BOLSS	Description
L	L=LG Innotek
F	F=Medium Beam Spread
1X	1X=One
12	9=9w, 12=12w
U	U=120-277V
4K	3K=3000K, 4K=4000K, 57K=5700K, 65K=6500K
SS	SS=Stainless Steel
OPTIONS:	
SF	SF=Single Fuse
DF	DF=Double Fuse
SP	SP=Surge Protection
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts
BOLPC	Replacement Polycarbonate Lens

Example: *BOLL1X12U4KSSSP*



SPECIFICATIONS

Housing:
Formed 316 Stainless Steel Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance.
Reflector:
Cast Aluminum Louvers
Lens:
Clear Polycarbonate Lens
Mounting:
Mounting Kit with 8. Anchor Bolts (Included)
LG LED Module:
Luminous Flux: See Chart
CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K
Operating Temperature: -40 . 50oC

50,000 Hours
Module has IP67 Rating
RoHS Compliant
Wattage:
LED: 1 x 9 or 12w
Driver:
Electronic Driver, 120-277V, 50/60Hz
Listing & Ratings:
CSA: Listed for Wet Locations
Options:
Dimmable Driver
2.5KV Surge Protection
Bollards Can Be Cut To Custom Lengths Upon Request.

**LED Dome Stainless Steel Bollard with Louvers
(LG)**

Model: BOLSS

Formed 316 Stainless Steel Housing with Flush Mounting Base and Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance. Cast Aluminum Louvers with Clear Polycarbonate Lens.
LED: 1 x 9 or 12w

**Total
Luminous Flux
per Module
Optic Type
C F I**

	12w	9w	12w	9w	12w	9w
CCT						
6500K	1288	850	1345	888	1296	856
5700K	1288	850	1345	888	1296	856
4000K	1076	710	1100	726	1088	718
3000K	1000	690	1030	705	1015	710



SPECIFICATIONS

Housing:
Formed 316 Stainless Steel Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance.
Reflector:
Cast Aluminum Louvers
Lens:
Clear Polycarbonate Lens
Mounting:
Mounting Kit with 8. Anchor Bolts (Included)
LG LED Module:
Luminous Flux: See Chart
CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K
Operating Temperature: -40 . 50oC

50,000 Hours
Module has IP67 Rating
RoHS Compliant
Wattage:
LED: 1 x 9 or 12w
Driver:
Electronic Driver, 120-277V, 50/60Hz
Listing & Ratings:
CSA: Listed for Wet Locations
Options:
Dimmable Driver
2.5KV Surge Protection
Bollards Can Be Cut To Custom Lengths
Upon Request.