

LED Dome Bollard with LED Cone Reflector

Model: BORL

Extruded aluminum dome-top LED bollard with powdercoat finish, aluminum cone reflector, and clear polycarbonate lens. Housing features a flush mounting base, vandal resistant screws, and an internal ballast tray. Mounting kit with 8" anchor bolts included. Maximum 2x15w LED

ORDERING

BORL	Description
X	Xicato
3X	Three LED Modules
2X	Two LED Modules
15H	15 Watts *Not available in 3 module units
7H	7.5 Watts
U	120, 277, 347 or 480 Volts
4	4000K
Z	Bronze
W	White
B	Black
OPTIONS:	
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts
BOLPC	Replacement Polycarbonate Lens

Example: *BORLX3X7HU4W*



SPECIFICATIONS

Housing:
Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance
Reflector:
Specially Designed Aluminum Cone Reflector for LED.
Lens:
Clear Polycarbonate Lens
Mounting:
Mounting Kit with 8" Anchor Bolts (Included)
Xicato LED Module:
Luminous Flux: 1070lm @ 500mA (83 lpw), 780lm

@ 350mA (88 lpw)
CRI: ≥80, CCT: 4000K
Operating Temperature: -40°C to 80°C {@ Tc}
50,000 Hours
Module has IP66 Rating
RoHS Compliant
1x2 MacAdam Ellipse Color Specification
Wattage:
LED: 2 x 7.5 or 15w, 3 x 7.5w
Listing & Ratings:
CSA: Listed for Wet Locations
Custom Colors Available Upon Request.
Bollards Can Be Cut To Custom Lengths Upon Request.

LED Dome Bollard with LED Cone Reflector

Model: BORL

Extruded aluminum dome-top LED bollard with powdercoat finish, aluminum cone reflector, and clear polycarbonate lens. Housing features a flush mounting base, vandal resistant screws, and an internal ballast tray. Mounting kit with 8" anchor bolts included. Maximum 2x15w LED

**Total
Luminous Flux
per Module
Optic Type
C F I**

	12w	9w	12w	9w	12w	9w
CCT						
6500K	1288	850	1345	888	1296	856
5700K	1288	850	1345	888	1296	856
4000K	1076	710	1100	726	1088	718



SPECIFICATIONS

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance

Reflector:

Specially Designed Aluminum Cone Reflector for LED.

Lens:

Clear Polycarbonate Lens

Mounting:

Mounting Kit with 8" Anchor Bolts (Included)

LG LED Module:

Luminous Flux: See Chart

CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K

Operating Temperature: -40 ~ 50°C

50,000 Hours

Module has IP67 Rating

RoHS Compliant

Wattage:

LED: 1 x 9 or 12w

Driver:

Electronic Driver, 120-277V, 50/60Hz

Listing & Ratings:

CSA: Listed for Wet Locations

Options:

Dimmable Driver

2.5KV Surge Protection

Custom Colors Available Upon Request.

Bollards Can Be Cut To Custom Lengths