

# Dome Stainless Steel Bollard with LED Cone Reflector (LG)

Model: BORLSS

Formed 316 Stainless Steel Housing with Flush Mounting Base and Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance. Specially Designed Aluminum Cone Reflector for LED. Clear Polycarbonate Lens Mounting Kit with 8" (200 mm) Anchor Bolts (Included). LED: 1 x 9 or 12w

## ORDERING

BORLLSS	Description
L	LG Innotek
F	Medium Beam Spread
1x	One Module
12	12 Watts
9	9 Watts
U	120-277
4K	3K=3000K, 4K=4000K, 57K=5700K, 65K=6500K
SS	Stainless Steel
OPTIONS:	
SF	Single Fuse
DF	Double Fuse
SP	Surge Protection
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts
BOLPC	Replacement Polycarbonate Lens



Example: BOLX3X7HU4W

## SPECIFICATIONS

Housing:  
Formed 316 Stainless Steel Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance.  
Reflector:  
Specially Designed Aluminum Cone Reflector for LED.  
Lens:  
Clear Polycarbonate Lens  
Mounting:  
Mounting Kit with 8" Anchor Bolts (Included)  
LG LED Module:  
Luminous Flux: See Chart  
CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K

Operating Temperature: -40 ≈ 50°C  
50,000 Hours  
Module has IP67 Rating  
RoHS Compliant  
Wattage:  
LED: 1 x 9 or 12w  
Driver:  
Electronic Driver, 120-277V, 50/60Hz  
Listing & Ratings:  
CSA: Listed for Wet Locations  
Options:  
Dimmable Driver  
2.5KV Surge Protection  
Bollards Can Be Cut To Custom Lengths

**Dome Stainless Steel Bollard with LED Cone Reflector (LG)**

**Model: BORLSS**

Formed 316 Stainless Steel Housing with Flush Mounting Base and Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance. Specially Designed Aluminum Cone Reflector for LED. Clear Polycarbonate Lens Mounting Kit with 8" (200 mm) Anchor Bolts (Included). LED: 1 x 9 or 12w

Total Luminous Flux per Module Optic Type C F I	12w		9w		12w		9w	
	12w	9w	12w	9w	12w	9w	12w	9w
<b>CCT</b>								
6500K	1288	850	1345	888	1296	856		
5700K	1288	850	1345	888	1296	856		
4000K	1076	710	1100	726	1088	718		
3000K	1000	690	1030	705	1015	710		



**SPECIFICATIONS**

Housing: Formed 316 Stainless Steel Housing with Flush Mounting Base & Vandal-Resistant Screws, Domed Top, Internal Ballast Tray for Easy Maintenance.	50,000 Hours Module has IP67 Rating RoHS Compliant
Reflector: Specially Designed Aluminum Cone Reflector for LED.	Wattage: LED: 1 x 9 or 12w
Lens: Clear Polycarbonate Lens	Driver: Electronic Driver, 120-277V, 50/60Hz
Mounting: Mounting Kit with 8" Anchor Bolts (Included)	Listing & Ratings: CSA: Listed for Wet Locations
LG LED Module: Luminous Flux: See Chart CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K Operating Temperature: -40 ≈ 50°C	Options: Dimmable Driver 2.5KV Surge Protection Bollards Can Be Cut To Custom Lengths Upon Request.