

LED Square Flat Top Bollard with IES Type III Glass

Model: BOSFG33

Square extruded aluminum flat-top LED bollard with powdercoat finish, IES Type III clear prismatic borosilicate glass refractor, and clear polycarbonate lens. Housing features a flush mounting base, vandal resistant screws, and an internal ballast tray. Mounting kit with 8" anchor bolts included. Maximum 2x15w LED.

ORDERING

BOSFG33	Description
X	X=Xicato
3x	2X=Two, 3X=Three
15H	15=15w* *15w Not Available for 3 Module Units.
7.5H	7H=7.5w
U	U=120-277V, 347=347V, 480=480V
4	4=4000K
Z	Z=Bronze
W	W=White,
B	B=Black
OPTIONS:	
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts
BOLPC	Replacement Polycarbonate Lens

Example:
BOSFG33X3X7HU4Z



SPECIFICATIONS

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Flat Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance

Refractor:

IES Type III Clear Prismatic Borosilicate Glass Refractor

Lens:

Clear Polycarbonate Lens

Mounting:

Mounting Kit with 8" Anchor Bolts (Included)

Xicato LED Module:

Luminous Flux: 1070lm @ 500mA (83 lpw),
780lm @ 350mA (88 lpw)
CRI: ≥80, CCT: 4000K
Operating Temperature: -40°C to 80°C (@ Tc)
50,000 Hours

Module has IP66 Rating

RoHS Compliant

1x2 MacAdam Ellipse Color Specification

Wattage:

LED: 2 x 7.5 or 15w, 3 x 7.5w

Listing & Ratings:

CSA: Listed for Wet Locations

Custom Colors Available Upon Request.

Bollards Can Be Cut To Custom Lengths

LED Square Flat Top Bollard with IES Type III Glass

Model: BOSFG33

Square extruded aluminum flat-top LED bollard with powdercoat finish, IES Type III clear prismatic borosilicate glass refractor, and clear polycarbonate lens. Housing features a flush mounting base, vandal resistant screws, and an internal ballast tray. Mounting kit with 8" anchor bolts included. Maximum 2x15w LED.



SPECIFICATIONS

Housing: Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Flat Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance	780lm @ 350mA (88 lpw) CRI: ≥ 80 , CCT: 4000K Operating Temperature: -40°C to 80°C {@ Tc} 50,000 Hours Module has IP66 Rating RoHS Compliant
Refractor: IES Type III Clear Prismatic Borosilicate Glass	1x2 MacAdam Ellipse Color Specification
Refractor	Wattage: LED: 2 x 7.5 or 15w, 3 x 7.5w
Lens: Clear Polycarbonate Lens	Listing & Ratings: CSA: Listed for Wet Locations Custom Colors Available Upon Request. Bollards Can Be Cut To Custom Lengths Upon Request.
Mounting: Mounting Kit with 8" Anchor Bolts (Included)	
Xicato LED Module: Luminous Flux: 1070lm @ 500mA (83 lpw),	