

LED Square Flat Top Bollard with Round Louvers

Model: BOSFLR3

Square extruded aluminum flat-top LED bollard with powdercoat finish, cast aluminum louvers, and clear polycarbonate lens. Housing features a flush mounting base, vandal resistant screws, and an internal ballast tray. Mounting kit with 8" anchor bolts included. Maximum 2x15w LED.

ORDERING

BOSFLR3	Description
X	X=Xicato
3x	2X=Two, 3X=Three
15H	15=15w* *15w Not Available for 3 Module Units.
7.5H	7H=7.5w
U	U=120-277V, 347=347V, 480=480V
4	4=4000K
Z	Z=Bronze
W	W=White,
B	B=Black
OPTIONS:	
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts
BOLPC	Replacement Polycarbonate Lens

Example: BOSFLR3X3X7HU4Z

SPECIFICATIONS



Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Flat Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance

Reflector:

Round Cast Aluminum Louvers

Lens:

Clear Polycarbonate Lens

Mounting:

Mounting Kit with 8" Anchor Bolts (Included)

Xicato LED Module:

Luminous Flux: 1070lm @ 500mA (83 lpw),

780lm @ 350mA (88 lpw)

CRI: ≥80, CCT: 4000K

Operating Temperature: -40°C to 80°C { @ Tc }

50,000 Hours

Module has IP66 Rating

RoHS Compliant

1x2 MacAdam Ellipse Color Specification

Wattage:

LED: 2 x 7.5 or 15w, 3 x 7.5w

Listing & Ratings:

CSA: Listed for Wet Locations

Custom Colors Available Upon Request.

Bollards Can Be Cut To Custom Lengths

Upon Request.

LED Square Flat Top Bollard with Round Louvers

Model: BOSFLR3

Square extruded aluminum flat-top LED bollard with powdercoat finish, cast aluminum louvers, and clear polycarbonate lens. Housing features a flush mounting base, vandal resistant screws, and an internal ballast tray. Mounting kit with 8" anchor bolts included. Maximum 2x15w LED.



SPECIFICATIONS

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Flat Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray for Easy Maintenance

Reflector:

Round Cast Aluminum Louvers

Lens:

Clear Polycarbonate Lens

Mounting:

Mounting Kit with 8" Anchor Bolts (Included)

Xicato LED Module:

Luminous Flux: 1070lm @ 500mA (83 lpw),

780lm @ 350mA (88 lpw)

CRI: ≥80, CCT: 4000K

Operating Temperature: -40°C to 80°C { @ Tc }

50,000 Hours

Module has IP66 Rating

RoHS Compliant

1x2 MacAdam Ellipse Color Specification

Wattage:

LED: 2 x 7.5 or 15w, 3 x 7.5w

Listing & Ratings:

CSA: Listed for Wet Locations

Custom Colors Available Upon Request.

Bollards Can Be Cut To Custom Lengths