

LED Square Bollard with LED Cone Reflector

Model: BOSFRLX

Square extruded aluminum flat-top LED bollard with powdercoat finish, aluminum cone reflector, and clear polycarbonate lens. Housing features a flush mounting base, vandal resistant screws, and an internal ballast tray. Mounting kit with 8" anchor bolts included. Maximum 2x15w LED

ORDERING

BOSFRLX	Description
L	L=LG Innotek
F	F=Medium Beam Spread
1X	1X=One
12	9=9W, 12=12W
U	U=120-277V
4K	3K=3000K, 4K=4000K, 57K=5700K, 65K=6500K
Z	Z=Bronze
W	W=White,
B	B=Black
OPTIONS:	
SF	SF=Single Fuse
DF	DF=Double Fuse
SP	SP=Surge Protection
BOLAN4	Mounting Kit, Includes Bracket & Three (3) 4" Anchor Bolts
BOLAN8	Mounting Kit, Includes Bracket & Three (3) 8" Anchor Bolts
BOLAN12	Mounting Kit, Includes Bracket & Three (3) 12" Anchor Bolts
BOLAN15	Mounting Kit, Includes Bracket & Three (3) 15" Anchor Bolts
BOLPCS	Replacement Polycarbonate Lens Square



Example:
BOSFRLLF1X12U4KZSP

SPECIFICATIONS

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Flat Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray.

Reflector:

Specially Designed Aluminum Cone Reflector for LED.

Lens:

Clear Polycarbonate Lens

Mounting:

Mounting Kit with 8" Anchor Bolts (Included)

LG LED Module:

Luminous Flux: See Chart

CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K

Operating Temperature: -40 = 50°C

50,000 Hours

Module has IP67 Rating

RoHS Compliant

Wattage:

LED: 1 x 9 or 12w

Driver:

Electronic Driver, 120-277V, 50/60Hz

Listing & Ratings:

CSA: Listed for Wet Locations

Options:

Dimmable Driver

2.5KV Surge Protection

Custom Colors Available Upon Request.

Bollards Can Be Cut To Custom Lengths

Upon Request.

LED Square Bollard with LED Cone Reflector

Model: BOSFRLX

Square extruded aluminum flat-top LED bollard with powdercoat finish, aluminum cone reflector, and clear polycarbonate lens. Housing features a flush mounting base, vandal resistant screws, and an internal ballast tray. Mounting kit with 8" anchor bolts included. Maximum 2x15w LED



SPECIFICATIONS

Housing:

Extruded Aluminum Housing with Flush Mounting Base & Vandal-Resistant Screws, Flat Top, Powdercoat Finish Over a Chromate Conversion Coating, Internal Ballast Tray.

Reflector:

Specially Designed Aluminum Cone Reflector for LED.

Lens:

Clear Polycarbonate Lens

Mounting:

Mounting Kit with 8" Anchor Bolts (Included)

LG LED Module:

Luminous Flux: See Chart

CRI: 70+, CCT: 3000K, 4000K, 5700K or 6500K

Operating Temperature: -40 ~ 50°C

50,000 Hours

Module has IP67 Rating

RoHS Compliant

Wattage:

LED: 1 x 9 or 12w

Driver:

Electronic Driver, 120-277V, 50/60Hz

Listing & Ratings:

CSA: Listed for Wet Locations

Options:

Dimmable Driver

2.5KV Surge Protection

Custom Colors Available Upon Request.

Bollards Can Be Cut To Custom Lengths